



TRU-HOLD® ANCHOR BOLT HOLDER INSTALLATION DETAILS



1 Choose the right color-coded tube for the size of the hardware.



2 Screw the tube into the base bracket.



3 Do not forget to install the thumbscrew on the tube



4 Slide the hardware into the opening on the bottom of the tube



5 Adjust the required direction and height and screw the thumb screw to hold the hardware



6 Place Tru-Hold® on the form with the identification layout* located on the center of elongated layout opening



7 Nail down Tru-Hold® on the form by following the stop and step face for different size of form (2x4 or 2x6 lumber)



8 **READY-** just pour the concrete and let it semidry before taking off the Tru-Hold® from the hardware

P/N	Definition	Color
20001	BRACKET	Silver
20003	THUMB SCREW	Silver
20002-A	TUBE-1/2"	Yellow
20002-AL	TUBE-1/2" LONG1)	Yellow
20002-B	TUBE-5/8"	Blue
20002-BL	TUBE-5/8" LONG1)	Blue
20002-C	TUBE-3/4"	Red
20002-CL	TUBE-3/4" LONG1)	Red
20002-D	TUBE-7/8"	Green
20002-DL	TUBE-7/8" LONG1)	Green
20002-E	TUBE-1"	White
20002-EL	TUBE-1" LONG1)	White

Warranty/Limited Liability

ThinX, Corp. warrants its products to be free from defects in material or manufacturing. ThinX, Corp. products are further warranted for adequacy of design when used in accordance with design limits when properly specified, installed, and maintained. This warranty does not apply to products used not in compliance with specific applications and installation procedures or modified products, or to deterioration due to environmental conditions.

Properly-installed ThinX, Corp. products will perform in accordance with specifications set forth in the applicable ThinX Corp information sheet. Additional performance limitations for specific products may be listed on the applicable catalog pages.

All warranty obligations of ThinX, Corp. shall be limited, at the discretion of ThinX, Corp. to repair or replacement of the defective part(s). These remedies shall constitute ThinX, Corp.s sole's obligation and sole remedy of purchaser under this warranty. In no event will ThinX, Corp. be responsible for incidental, consequential, or special loss or damage, however caused.

This warranty is expressly in lieu of all other warranties, expressed or implied, including warranties of merchantability or fitness for a particular purpose, all such other warranties being hereby expressly excluded. This warranty may change periodically - consult this for current information.



ALL PRODUCTS START IN THE FIELD,
DESIGNED BY PROFESSIONALS IN THE FIELD,
FOR THOSE WHO WORK IN THE FIELD

TRU-HOLD® CONCRETE HARDWARE ANCHORING SYSTEM

Tube - Thread Protector

- Color Coded for different sizes of hardware
- Available in different lengths for different types of pours
- Durable and light - Thermoplastic – Rust Resistant
- Low replacement cost
- Interchangeable – One base for different sizes and lengths of thread protector
- Keeps the hardware straight and maintains the vertical distance of the hardware
- Protects the threads on the hardware from concrete spills

Thumb Screw

- Holds the hardware at the right height and direction
- Prevents the hardware from rotational movement

Rigid ALUMINUM EXTENSION ARM BASE

- Strong and firm – will not deflect due to the weight of the hardware and concrete pressure
- Light and Durable – made from aluminum for lightness and rust resistance
- Install it once and leave it

LAYOUT OPENING

- Minimizes errors by missing or placing the hardware incorrectly
- Maximizes high skill labor productivity by performing only the layout and lets the helper install Tru-Hold® and the hardware.

STEP AND STOP

- Automatically secures the position of Tru-Hold® to maintain the horizontal distance of the hardware for different types of lumber (2x6 and 2x8)

APERTURES

- Attach the Tru-Hold® with the hardware installed firmly on the form
- A few apertures on different locations to accommodate different jobs and form conditions

MARKING / SIGN:

- Simple guide to install the hardware
- Hardware installation procedure from manufacturer should supersede the instruction on the marking/sign.

Thinx, Corp - Baldwin Park, CA

Customer Satisfaction is our number one Goal.

Please direct your comments and/or questions by phone, fax, or e-mail at:

Phone (626) 337-6836/7

Fax (626) 337-6831

e-mail: info@thinxcorp.com